



APPLICATIONS

The ETDR 10 has been designed for quick and accurate fault location and qualification of balanced telecommunication cables.

The various measuring modes provide accurate location of discontinuities and errors like open circuit, wet section, loose contact etc.

ETDR 10 employs optimized pulsing and sampling methods, supported with advanced filtering and signal processing techniques, to reach the maximum measurement range and clean waveform for easier fault interpretation.

ETDR 10 is designed for ease-of-use. If you select the cable type from the on board cable library and set the measurement range covering the length of the cable to be tested, V/2, gain, pulse width, and the distance dependent compensation of cable attenuation are automatically set as default.

3 to 10 ns pulse widths for close-in resolution. Faults as near as 0.5 m from the pedestal can be easily located.

30 ns to 6 μs pulse widths for the test of non-loaded cables.

330 μs pulse width for the test of loaded cables. Help facility with sample traces and useful topic related information.

PC program is provided for post processing and transfer of test results via USB port.

FEATURES

- TDR for balanced cables
- Easy to operate
- Small size, suitable for using in the field
- Widest range in a hand-held cable fault locator up to 32 km
- Language selectable: English, German, Russian
- Dual balanced input enables
 - Examination of live lines
 - Comparison of two live lines
 - Difference between two live lines
 - Comparison of live line to memory
 - Difference between live line and memory
 - Location of crosstalk points
 - Location of intermittent faults
- 100 memories for waveform and setting storage
- Clear waveform display of full trace for accurate diagnosis, 320 x 240 LCD color display with backlight
- Zoom for detailed examination
- Cable library for standard and user defined cable types
- Results can be transferred to PC via USB
- Internal rechargeable NiMH battery pack
- Unit adjustment between V/2 and VOP
- Special program for performing the yearly calibration

SPECIFICATIONS

Ranges (V/2=100 or V/2=10 for loaded cable)

- | | |
|-------------------------------|---------|
| 1. For non loaded cable | 16 m |
| 2. For non loaded cable | 32 m |
| 3. For non loaded cable | 64 m |
| 4. For non loaded cable..... | 160 m |
| 5. For non loaded cable..... | 320 m |
| 6. For non loaded cable..... | 640 m |
| 7. For non loaded cable..... | 1600 m |
| 8. For non loaded cable..... | 3200 m |
| 9. For all cables..... | 6400 m |
| 10. For all cables..... | 16000 m |
| 11. For all cables..... | 32000 m |
- (Maximum range depends on cable features)

Evaluation of results

with cursor and marker in meters

Zoom

SelectableOFF, 2.5, 5

Resolution

with zoom.....0.06% of range
without zoom.....0.3% of range

Accuracy

Sampling0.01 m
Fault location.....0.2% of range



Propagation velocity

For non loaded cables
 V/2 45 to 150 m/ μ s
 VOP 30 to 99 %
 For non loaded cables
 V/2 1.2 to 30 m/ μ s
 VOP 0.8 to 20 %

Measuring modes

L1 L2	Test of a single pair
L1 LONG TIME L2 LONG TIME	Location of intermittent faults
XTALK	Transmit on L2, receive on L1
L1 & L2 L1 - L2	Comparison of two pairs
L1 & MEMORY L1 - MEMORY	Comparison with memory

Pulse characteristics

Amplitude: . max 12V peak to peak into 120 Ohm
 Widths for non loaded cables:
 3, 6, 10, 30, 60, 100, 300, 600 ns 1, 3, 6 μ s
 Width for loaded cables: 330 μ s,
 The provided pulse width changed with range.
 Amplitude:peak to peak 1.3 to 12V into 120 Ohm
 The pulse amplitude changed with gain and width.

Gain control

Range 0 to 90 dB
 Steps 6 dB/step

Line connection

Impedance 120 Ohm balanced
 Input protection 350V RMS 50 Hz 500 V DC
 Balance control 50 to 270 Ohm

Memory locations

For waveforms 50
 For setups 10
 For user stored PVF values 10
 For standard cable parameters 30

General specifications

Power supply
 Internal rechargeable NIMH battery pack
 Operation time approx. 8 hours
 (60 % duty time)
 Charging (without taking the battery pack out)
 From 230 V mains with mains adapter
 From 12 V car battery with car adapter
 Charging time approx. 3 hours
 (Fast charging mode)
 Display 320x240 Color LCD
 Connectors
 For mains or 12V car adapter 2.1/5.5 mm coaxial
 L1 and L2 line connectors .4 mm banana sockets
 USB B USB 1.1 device port to connect PC
 Ambient temperature range
 Operating -10 to +50°C
 Storage and transport -20 to +70°C
 Dimensions 200 x 100 x 40 mm
 Weight 0.8 kg

Ordering information

TIME DOMAIN REFLECTOMETER
ETDR 10 418-000-000
 Including:
 Operating Manual OM 418-000-000E
 Short form op. instructions ML 418-000-000E
 Calibration Certificate CC 418-000-000E
 CD (xxx version) CD 418-000-000E
 Measuring Cable Set 365-500-000
 USB cable Y 107-389
 Mains adapter
 European version or Y 146-001
 UK version or Y 146-020
 US version Y 146-022
 Cable for car battery connection 326-210-000
 Battery (built-in) 367-000-000
 Carrying case Y 147-007
 Shoulder bag Y 147-024
 PC software for data transfer SW 418-510-000
 Option:
 ECA 10 Coaxial Adapter 378-000-000

